



※ \*(198) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SH2L			
MATERIAL			HOUSING-AL			
			LENS-PC			
			REFLECTOR-HEAT RESISTANT ABS			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	0.08W	MAX. 0.300A	
			DC24V		MAX. 0.200A	
			AC110V		MAX. 0.060A	
			AC220V		MAX. 0.030A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			LED STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-								
FOR LINEAR DIMENSIONS		f	m	⊙	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE								
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE									
	3~6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30									
	6~30	±0.1	±0.2	±0.5	±1	TITLE SH2L OUTLINE DRAWING														
	30~120	±0.15	±0.3	±0.8	±1.5							MODEL SH2L								
	120~400	±0.2	±0.5	±1.2	±2.5															
400~1000	±0.3	±0.8	±2	±4																
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°							DWG. NO. SH2L_OUT									
	10~50	±0°30'	±1°	±2°																
	50~120	±0°20'	±0°30'	±1°													SCALE N/S			
	120~400	±0°10'	±0°13'	±0°30'																
								REV 00		SHEET 1/1										

A4(297X210)