



※ \*(198) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			SH2T			
MATERIAL			HOUSING-AL			
			LENS-PC			
			REFLECTOR-PC			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
REV. PER MIN			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	15W	MAX. 1.544A	
			DC24V		MAX. 0.766A	
			AC110V		MAX. 0.204A	
			AC220V		MAX. 0.102A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-					
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE					
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30						
	3~6			±0.3	±0.5												
	6~30	±0.1	±0.2	±0.5	±1	TITLE SH2T OUTLINE DRAWING											
	30~120	±0.15	±0.3	±0.8	±1.5							MODEL SH2T					
	120~400	±0.2	±0.5	±1.2	±2.5												
400~1000	±0.3	±0.8	±2	±4	DWG. NO. SH2T_OUT												
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'							±3°						
	10~50	±0°30'		±1°							±2°						
	50~120	±0°20'		±0°30'							±1°						
	120~400	±0°10'		±0°13'							±0°30'						
						SCALE N/S		SIZE A4		REV 00		SHEET 1/1					

**Qlight**

A4(297X210)