



※ \*(198) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			SH2TLR				
MATERIAL			HOUSING-AL				
			LENS-PC				
			REFLECTOR-PC				
			PROTECTION CAGE-SUS316L				
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )				
REV. PER MIN.			120 ~ 140				
USE VOLT.	LED	CURRENT	DC12V		1W	MAX. 0.422A	
			DC24V			MAX. 0.266A	
			AC110V			MAX. 0.082A	
			AC220V			MAX. 0.041A	
PROTECTION GRADE			WATER & DUST PROOF IP66				
CABLE ENTRY			1/2" PF				
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2				
ACTION			LED REVOLVING WARNING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1	TITLE SH2TLR OUTLINE DRAWING		MODEL SH2TLR				
	30~120	±0.15	±0.3	±0.8	±1.5				DWG. NO. SH2TLR_OUT			
	120~400	±0.2	±0.5	±1.2	±2.5					SCALE N/S	SIZE A4	REV 00
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4							
	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							

**Qlight**

SCALE N/S SIZE A4 REV 00 SHEET 1/1

A4(297X210)