



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			SNE-S			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED GLASS			
			PROTECTION CAGE-SUS316L			
			-			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHING PER MIN.			60~80			
USE VOLT.	XENON	CURRENT	DC12V DC24V	6W	MAX. 0.435A	
			AC110V		0.075A	
			AC220V		0.060A	
			PROTECTION GRADE			WATER & DUST PROOF IP66
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1		TITLE  SNE-S OUTLINE DRAWING		MODEL  SNE-S			
	30~120	±0.15	±0.3	±0.8	±1.5					DWG. NO.  SNE-S_OUT		
	120~400	±0.2	±0.5	±1.2	±2.5						SCALE N/S	SIZE A4
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							

**Qlight**

A4(297X210)