



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			S60ADL			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	0.08W	MAX. 0.166A	
			DC24V		MAX. 0.125A	
			AC110V		MAX. 0.043A	
			AC220V		MAX. 0.022A	
VOLUME			MAX. 100dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			10 X 10			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-		1		-	
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	±0.5			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6	±0.05	±0.1	±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1			TITLE		MODEL			
	30~120	±0.15	±0.3	±0.8	±1.5			S60ADL		S60ADL			
	120~400	±0.2	±0.5	±1.2	±2.5			OUTLINE DRAWING		S60ADL_OUT			
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°			Qlight		DWG. NO.			
	10~50	±0°30'		±1°	±2°					S60ADL_OUT			
	50~120	±0°20'		±0°30'	±1°					SCALE		REV	
	120~400	±0°10'		±0°13'	±0°30'					N/S		A4	
										SIZE		00	
										SHEET		1/1	

A4(297X210)