



※ *(227) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			SHDS			
MATERIAL			HOUSING-AL			
			LENS-PC			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	6W	MAX. 2.933A	
			DC24V		MAX. 1.411A	
			AC110V		MAX. 0.360A	
			AC220V		MAX. 0.220A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH
FOR LINEAR DIMENSIONS		f	m	(C)	v	
	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4	
	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

-	-	-	-	1	-	
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
TITLE			MODEL			
SHDS OUTLINE DRAWING			SHDS			
			DWG. NO.			
			SHDS_OUT			
SCALE		SIZE	REV	SHEET		
N/S		A4	00	1/1		