



※ *(227) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			SHD2			
MATERIAL			HOUSING-AL			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	15W	MAX. 5.966A	
			DC24V		MAX. 2.755A	
			AC110V		MAX. 0.648A	
			AC220V		MAX. 0.324A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓢ	v
	3~6	±0.05	±0.1	±0.2	-
	6~30	±0.1	±0.2	±0.3	±0.5
	30~120	±0.15	±0.3	±0.5	±1
	120~400	±0.15	±0.3	±0.8	±1.5
	400~1000	±0.2	±0.5	±1.2	±2.5
FOR ANGULAR DIMENSIONS	0~10	±0.3	±0.5	±1.2	±2.5
	10~50	±0.8	±1	±2	±4
	50~120	±1°	±1°30'	±1°	±2°
	120~400	±0°30'	±0°30'	±0°30'	±1°
	120~400	±0°20'	±0°10'	±0°13'	±0°30'

SURFACE FINISH		-		1	
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y
DSND BY	CHKD BY	CHKD BY		APRV BY	VIEW
S.H.KIM	J.H.PARK			J.K.HAN	3
TITLE		SHD2 OUTLINE DRAWING		MODEL SHD2	
		DWG. NO.		SHD2_OUT	
		SCALE	SIZE	REV	SHEET
		N/S	A4	00	1/1