



※ *(227) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SHD2LR			
MATERIAL			HOUSING-AL			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	LED	CURRENT	DC12V	1W	MAX. 4.844A	
			DC24V		MAX. 2.255A	
			AC110V		MAX. 0.535A	
			AC220V		MAX. 0.267A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v
	0.5~3	±0.05	±0.1	±0.2	-
	3~6			±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4
	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE FINISH	-	-	-		-	1	-	
	Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE	
	DSND BY S.H.KIM		CHKD BY J.H.PARK		CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30
	TITLE SHD2LR OUTLINE DRAWING				MODEL SHD2LR			
					DWG. NO. SHD2LR_OUT			
					SCALE N/S	SIZE A4	REV 00	SHEET 1/1