



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			S60ADB			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	BULB	CURRENT	DC12V	10W	MAX. 1.008A	
			DC24V		MAX. 0.556A	
			AC110V		MAX. 0.127A	
			AC220V		MAX. 0.064A	
VOLUME			MAX. 100dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			10 X 10			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			BULB STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	±0.5		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5		S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		S60ADB			S60ADB		
	120~400	±0.2	±0.5	±1.2	±2.5		OUTLINE DRAWING			S60ADB_OUT		
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4					DWG. NO.		
	0~10	±1°		±1°30'	±3°					S60ADB_OUT		
	10~50	±0°30'		±1°	±2°		SCALE			SIZE	REV	SHEET
	50~120	±0°20'		±0°30'	±1°		N/S			A4	00	1/1
	120~400	±0°10'		±0°13'	±0°30'							