



※ *(227) represents size without protection cage.

| MARK | DATE | REVISION | REVISER | APP. BY |
|------|------|----------|---------|---------|
| ① | | | | |
| ② | | | | |
| ③ | | | | |

| | | | | | | |
|-------------------|-----|---------|---|-------|-------------|--|
| MODEL NO | | | SHD2L | | | |
| MATERIAL | | | HOUSING-AL | | | |
| | | | LENS-PC | | | |
| | | | REFLECTOR-HEAT RESISTING ABS | | | |
| | | | PROTECTION CAGE-SUS316L | | | |
| COLOR OF LENS | | | RED(), AMBER(), GREEN(), BLUE() | | | |
| FLASHING PER MIN. | | | 60 ~ 80 | | | |
| USE VOLT. | LED | CURRENT | DC12V | 0.08W | MAX. 4.722A | |
| | | | DC24V | | MAX. 2.188A | |
| | | | AC110V | | MAX. 0.513A | |
| | | | AC220V | | MAX. 0.256A | |
| PROTECTION GRADE | | | WATER & DUST PROOF IP66 | | | |
| CABLE ENTRY | | | 1/2" PF | | | |
| COLOR OF HOUSING | | | MUNSELL NO. 7.5BG 7/2 | | | |
| ACTION | | | LED STEADY/ FLASHING LIGHT | | | |

| ISO2768-1 : CLASS OF TOLERANCE | | | | | | SURFACE FINISH | - | - | - | - | 1 | - |
|--------------------------------|----------|--------|------|--------|--------|----------------|-----------------|----------|-------------|-----------|------|------------|
| FOR LINEAR DIMENSIONS | | f | m | ⌀ | v | | Nr. | DWG. NO. | TITLE/ NAME | MAT'L | QT'Y | REFERENCE |
| | 0.5~3 | ±0.05 | ±0.1 | ±0.2 | - | | DSND BY | CHKD BY | CHKD BY | APRV BY | VIEW | DATE |
| | 3~6 | | | ±0.3 | ±0.5 | | S.H.KIM | J.H.PARK | | J.K.HAN | 3 | 2016.08.30 |
| | 6~30 | ±0.1 | ±0.2 | ±0.5 | ±1 | | TITLE | | | MODEL | | |
| | 30~120 | ±0.15 | ±0.3 | ±0.8 | ±1.5 | | SHD2L | | | SHD2L | | |
| | 120~400 | ±0.2 | ±0.5 | ±1.2 | ±2.5 | | OUTLINE DRAWING | | | SHD2L_OUT | | |
| FOR ANGULAR DIMENSIONS | 400~1000 | ±0.3 | ±0.8 | ±2 | ±4 | | | | | DWG. NO. | | |
| | 0~10 | ±1° | | ±1°30' | ±3° | | | | | SCALE | | |
| | 10~50 | ±0°30' | | ±1° | ±2° | | | | | SIZE | | |
| | 50~120 | ±0°20' | | ±0°30' | ±1° | | | | | REV | | |
| | 120~400 | ±0°10' | | ±0°13' | ±0°30' | | | | | SHEET | | |
| | | | | | | | | | | 1/1 | | |

A4(297X210)