



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			S60ADS			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			-			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	4W	MAX. 0.550A	
			DC24V		MAX. 0.266A	
			AC110V		MAX. 0.088A	
			AC220V		MAX. 0.044A	
VOLUME			MAX. 100dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			10 X 10			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-	
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30		
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1	TITLE S60ADS OUTLINE DRAWING		MODEL S60ADS					
	30~120	±0.15	±0.3	±0.8	±1.5				DWG. NO. S60ADS_OUT	SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	120~400	±0.2	±0.5	±1.2	±2.5								
400~1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								

Qlight