



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			S100DLR				
MATERIAL			HOUSING-ABS				
			LENS-AS				
			REFLECTOR-HEAT RESISTING ABS				
REV. PER MIN.			120 ~ 140				
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()				
USE VOLT.	LED	CURRENT	DC12V		1W	MAX. 0.483A	
			DC24V			MAX. 0.327A	
			AC110V			MAX. 0.120A	
			AC220V			MAX. 0.060A	
KIND OF SOUND			WS	5 Warning Sounds			
			WM	5 Melodie			
			WA	5 Alarms			
			WV	5 Customizable sounds			
VOLUME			MAX. 105dB at 1m				
PROTECTION GRADE			WATER & DUST PROOF IP54				
CABLE ENTRY			ø10 LEAD HOLE				
COLOR OF HOUSING			MAKER STANDARD				
ACTION			LED REVOLVING WARNING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
	6~30	±0.1	±0.2	±0.5	±1	TITLE			MODEL			
	30~120	±0.15	±0.3	±0.8	±1.5	S100DLR			S100DLR			
	120~400	±0.2	±0.5	±1.2	±2.5	OUTLINE DRAWING			DWG. NO.			
400~1000	±0.3	±0.8	±2	±4				S100DLR_OUT				
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'				±3°	SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	10~50	±0°30'		±1°				±2°				
	50~120	±0°20'		±0°30'				±1°				
	120~400	±0°10'		±0°13'				±0°30'				