



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			S100DL				
MATERIAL			HOUSING-ABS				
			LENS-AS				
			REFLECTOR-HEAT RESISTING ABS				
FLASHING PER MIN.			60 ~ 80				
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()				
USE VOLT.	LED	CURRENT	DC12V ~ DC24V		0.08W	MAX. 0.410A	
			AC110V			0.115A	
			AC220V			0.060A	
KIND OF SOUND			WS	5 Warning Sounds			
			WM	5 Melodie			
			WA	5 Alarms			
			WV	5 Customizable sounds			
VOLUME			MAX. 105dB at 1m				
PROTECTION GRADE			WATER & DUST PROOF IP54				
CABLE ENTRY			ø10 LEAD HOLE				
COLOR OF HOUSING			MAKER STANDARD				
ACTION			LED STEADY/FLASHING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-		1		-	
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	±0.1	±0.2	±0.5	±1			TITLE S100DL OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4			MODEL S100DL					
	0~10	±1°	±1°30'	±3°				DWG. NO. S100DL_OUT					
	10~50	±0°30'	±1°	±2°									
	50~120	±0°20'	±0°30'	±1°									
	120~400	±0°10'	±0°13'	±0°30'									

Qlight

A4(297X210)