



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			S80AU			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	5W	MAX. 0.484A	
			DC24V		MAX. 0.310A	
			AC110V		MAX. 0.080A	
			AC220V		MAX. 0.040A	
VOLUME			MAX. 90dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			ø8 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3			±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6	±0.05	±0.1	±0.3	±0.5		S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		S80AU			S80AU		
	120~400	±0.2	±0.5	±1.2	±2.5		OUTLINE DRAWING			S80AU_OUT		
FOR ANGULAR DIMENSIONS	0~10			±2	±4					DWG. NO.		
	10~50			±1°	±2°					S80AU_OUT		
	50~120			±0°30'	±1°					SCALE	SIZE	REV
	120~400			±0°10'	±0°30'					N/S	A4	00
										SHEET		
										1/1		