



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			S100DS			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			-			
FLASHING PER MIN.			60 ~ 80			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
USE VOLT.	XENON	CURRENT	DC12V	6W	MAX. 1.330A	
			DC24V			
			AC110V		0.230A	
			AC220V		0.155A	
KIND OF SOUND			WS	5 Warning Sounds		
			WM	5 Melodie		
			WA	5 Alarms		
			WV	5 Customizable sounds		
VOLUME			MAX. 105dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			φ10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1	TITLE S100DS OUTLINE DRAWING		MODEL S100DS				
	30~120	±0.15	±0.3	±0.8	±1.5				DWG. NO. S100DS_OUT			
	120~400	±0.2	±0.5	±1.2	±2.5					SCALE N/S	SIZE A4	REV 00
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							

A4(297X210)