



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			S125D				
MATERIAL			HOUSING-ABS				
			LENS-AS				
			REFLECTOR-HEAT RESISTING ABS				
REV. PER MIN.			120 ~ 140				
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()				
USE VOLT.	BULB	CURRENT	DC12V		10W	MAX. 1.266A	
			DC24V			MAX. 0.766A	
			AC110V			MAX. 0.187A	
			AC220V			MAX. 0.094A	
KIND OF SOUND			WS	5 Warning Sounds			
			WM	5 Melodie			
			WA	5 Alarms			
			WV	5 Customizable sounds			
VOLUME			MAX. 105dB at 1m				
PROTECTION GRADE			WATER & DUST PROOF IP54				
CABLE ENTRY			ø10 LEAD HOLE				
COLOR OF HOUSING			MAKER STANDARD				
ACTION			BULB REVOLVING WARNING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓢ	v
	3~6	±0.05	±0.1	±0.2	-
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
	400~1000	±0.3	±0.8	±2	±4
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE FINISH

-	-	-	-	1	-
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
S125D OUTLINE DRAWING			S125D		
			DWG. NO.		
			S125D_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		

A4(297X210)