



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			S125DLR			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
REV. PER MIN.			120 ~ 140			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
USE VOLT.	LED	CURRENT	DC12V	1W	MAX. 0.483A	
			DC24V		MAX. 0.327A	
			AC110V		MAX. 0.120A	
			AC220V		MAX. 0.060A	
KIND OF SOUND			WS	5 Warning Sounds		
			WM	5 Melodie		
			WA	5 Alarms		
			WV	5 Customizable sounds		
VOLUME			MAX. 105dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			ø10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f	m	⌀	v
	3~6	±0.05	±0.1	±0.2	-
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
	400~1000	±0.3	±0.8	±2	±4
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE FINISH

-	-	-	-	1	-
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
S125DLR OUTLINE DRAWING			S125DLR		
Qlight			DWG. NO.		
			S125DLR_OUT		
SCALE		SIZE	REV	SHEET	
N/S		A4	00	1/1	

A4(297X210)