



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			S125DS				
MATERIAL			HOUSING-ABS				
			LENS-AS				
			-				
FLASHING PER MIN.			60 ~ 80				
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()				
USE VOLT.	XENON	CURRENT	DC12V ~ DC24V		6W	MAX. 1.330A	
			AC110V			0.230A	
			AC220V			0.155A	
KIND OF SOUND			WS	5 Warning Sounds			
			WM	5 Melodie			
			WA	5 Alarms			
			WV	5 Customizable sounds			
VOLUME			MAX. 105dB at 1m				
PROTECTION GRADE			WATER & DUST PROOF IP54				
CABLE ENTRY			ø10 LEAD HOLE				
COLOR OF HOUSING			MAKER STANDARD				
ACTION			XENON LAMP STROBE LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	±0.1	±0.2	±0.5	±1			TITLE S125DS OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5			MODEL S125DS					
	120~400	±0.2	±0.5	±1.2	±2.5			DWG. NO. S125DS_OUT					
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								
								SCALE	SIZE	REV	SHEET		
								N/S	A4	00	1/1		

A4(297X210)