



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO			SNES-S			
MATERIAL			HOUSING-AL			
			LENS-PC			
			PROTECTION CAGE-SUS316L			
			-			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	6W	0.655A	
			DC24V		0.500A	
			AC110V		0.104A	
			AC220V		0.066A	
SOUND			Buzzer	Warning Sounds		
VOLUME			MAX. 105dB			
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			NPT1/2"			
COLOR OF HOUSING			MUNSELL NO 7.5BG 7/2			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-		-		1		-	
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-			Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE	
	3~6	±0.05	±0.1	±0.3	±0.5			DSND BY	CHKD BY	CHKD BY		APRV BY	VIEW	DATE	
	6~30	±0.1	±0.2	±0.5	±1			S.H.KIM	J.H.PARK	J.K.HAN		J.K.HAN	3	2016.08.30	
	30~120	±0.15	±0.3	±0.8	±1.5			TITLE		SNES-S OUTLINE DRAWING		MODEL		SNES-S	
	120~400	±0.2	±0.5	±1.2	±2.5										
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°								DWG. NO.		SNES-S_OUT	
	10~50	±0°30'	±1°	±2°											
	50~120	±0°20'	±0°30'	±1°											
	120~400	±0°10'	±0°13'	±0°30'											

**Qlight**