



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			SEBA			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED GLASS			
			REFLECTOR-PC			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC24V	15W	MAX. 0.811A	
			AC110V		MAX. 0.291A	
			AC220V		MAX. 0.145A	
PROTECTION GRADE			WATER & DUST PROOF IP55			
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO.7.5BG 7/2			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-		1		-	
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2020.08.31
	6~30	±0.1	±0.2	±0.5	±1								
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4			TITLE		SEBA		MODEL	
	0~10	±1°		±1°30'	±3°			SEBA OUTLINE DRAWING		DWG. NO.		SEBA_OUT	
	10~50	±0°30'		±1°	±2°					SCALE		SHEET	
	50~120	±0°20'		±0°30'	±1°					N/S	A4	REV	1/1
	120~400	±0°10'		±0°13'	±0°30'							00	