



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SC2			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-PC			
			BRACKET-STEEL			
			HORN HOUSING-ABS			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	10W	MAX. 1.332A	
			DC24V		MAX. 0.832A	
			AC110V		MAX. 0.207A	
			AC220V		MAX. 0.103A	
VOLUME			MAX. 108dB			
PROTECTION GRADE			WATER & DUST PROOF IP44 (VARIOUS IP RATING AS PER CONFIGURATION)			
CABLE ENTRY			ø10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH						
FOR LINEAR DIMENSIONS		f	m	(C)	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	1
	0.5~3	±0.05	±0.1	±0.2	-							
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1		DSND BY	CHKD BY	TITLE/ NAME		APRV BY	VIEW
	30~120	±0.15	±0.3	±0.8	±1.5		S.H.KIM	J.H.PARK			J.K.HAN	3
	120~400	±0.2	±0.5	±1.2	±2.5							DATE
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4		TITLE		SC2		MODEL	
	0~10	±1°	±1°30'	±3°			OUTLINE DRAWING				SC2	
	10~50	±0°30'	±1°	±2°			Qlight		DWG. NO.		SC2_OUT	
	50~120	±0°20'	±0°30'	±1°					SCALE		SIZE	
	120~400	±0°10'	±0°13'	±0°30'					N/S		A4	
									REV	00	SHEET	1/1

A4(297X210)