

ST56L-W□ : AC
ST56LF-W□ : AC

LAYER	L
1	501
2	571
3	641
4	711
5	781



ST56L-W□ : DC
ST56LF-W□ : DC

LAYER	L
1	436
2	506
3	576
4	646
5	716

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			ST56L-W			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			POLE-AL			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE(), WHITE()			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	0.08W	MAX. 0.136A	LAYER1
			DC24V		MAX. 0.111A	LAYER1
			AC110V		MAX. 0.075A	LAYER1
			AC220V		MAX. 0.054A	LAYER1
KIND OF SOUND			WS	5 Pre-Recorded Warning Sounds		
			WM	5 Pre-Recorded Melodie		
			WA	5 Pre-Recorded Alarms		
VOLUME			MAX. 85dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP23			
CABLE ENTRY			ø8 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY/ FLASHING TOWER LAMP			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v	
	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4	
	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

-		-		-		1		-			
Nr.		DWG. NO.		TITLE/ NAME		MAT'L		QTY		REFERENCE	
DSND BY		CHKD BY		CHKD BY		APRV BY		VIEW		DATE	
S.H.KIM		J.H.PARK				J.K.HAN		3		2016.08.30	
TITLE						MODEL					
ST56L-W						ST56L-W					
OUTLINE DRAWING											
						DWG. NO.					
						ST56L-W_OUT					
SCALE			SIZE			REV			SHEET		
N/S			A4			00			1/1		

A4(297X210)