



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO		SM200		
MATERIAL		HOUSING-STEEL / AL		
USE VOLT.	CURRENT	DC24V	7.820A	
		AC110V	2.105A	
		AC220V	1.005A	
VOLUME		MAX. 120dB		
CABLE ENTRY		ø9 LEAD HOLE		
COLOR		RED		
RATING		10 MIN.		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	±0.1	±0.2	±0.5	±1			TITLE SM200 OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5			MODEL SM200					
	120~400	±0.2	±0.5	±1.2	±2.5			DWG. NO. SM200_OUT					
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°				Qlight					
	10~50	±0°30'	±1°	±2°						SCALE	SIZE	REV	SHEET
	50~120	±0°20'	±0°30'	±1°						N/S	A4	00	1/1
	120~400	±0°10'	±0°13'	±0°30'									

A4(297X210)