



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			S60LR			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN			120 ~ 140			
USE VOLT.	POWER LED	CURRENT	DC12V	1W	MAX. 0.183A	
			DC24V		MAX. 0.127A	
			AC110V		MAX. 0.040A	
			AC220V		MAX. 0.020A	
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			ø8 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			POWER LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-								
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE								
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30									
	3~6			±0.3	±0.5															
	6~30	±0.1	±0.2	±0.5	±1	TITLE S60LR OUTLINE DRAWING														
	30~120	±0.15	±0.3	±0.8	±1.5							MODEL S60LR								
	120~400	±0.2	±0.5	±1.2	±2.5															
400~1000	±0.3	±0.8	±2	±4	DWG. NO. S60LR_OUT															
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°																
	10~50	±0°30'	±1°	±2°																
	50~120	±0°20'	±0°30'	±1°													SCALE N/S			
	120~400	±0°10'	±0°13'	±0°30'																
				REV 00		SHEET 1/1														

Qlight

A4(297X210)