


MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			S80ALR			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
REV. PER MIN			120 ~ 140			
USE VOLT.	POWER LED	CURRENT	DC12V	1W	MAX. 0.183A	
			DC24V		MAX. 0.127A	
			AC110V		MAX. 0.035A	
			AC220V		MAX. 0.017A	
VOLUME			MAX. 90dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			ø8 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			POWER LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3			±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6	±0.05	±0.1	±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1			TITLE S80ALR OUTLINE DRAWING 					
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4			MODEL S80ALR S80ALR_OUT DWG. NO. SCALE N/S SIZE A4 REV 00 SHEET 1/1					
	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								