



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO			SEA-TI			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED CLASS			
			REFLECTOR-PC			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHING PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC24V	15W	0.720A	
			AC110V		0.170A	
			AC220V		0.110A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY K.H.PARK	CHKD BY J.K.HAN	CHKD BY 	APRV BY J.I.BAE	VIEW 3	DATE 2023. 5. 3.	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. SEA-TI_OUT			
	10~50	±0°30'		±1°	±2°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							