



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			SESALR-TI			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED CLASS			
			REFLECTOR-PC			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
REV. PER MIN.			120 ~ 140			
USE VOLT.	LED	CURRENT	DC24V	1W	1.190A	
			AC110V		0.300A	
			AC220V		0.180A	
VOLUME			MAX. 118dB			
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO.7.5BG 7/2			
ACTION			LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5		K.H.PARK	J.K.HAN		J.I.BAE	3	2023. 5. 3.
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		SESALR-TI			SESALR-TI		
	120~400	±0.2	±0.5	±1.2	±2.5		OUTLINE DRAWING			SESALR-TI_OUT		
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4					DWG. NO.		
	0~10	±1°		±1°30'	±3°					SCALE		
	10~50	±0°30'		±1°	±2°					SIZE		
	50~120	±0°20'		±0°30'	±1°					REV		
	120~400	±0°10'		±0°13'	±0°30'					SHEET		
										N/S		
										A4		
										00		
										1/1		