



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO			SESAL-TI			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED CLASS			
			REFLECTOR-HEAT RESISTANT ABS			
COLOR OF LENS.			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC24V	0.08W	1.130A	
			AC110V		0.270A	
			AC220V		0.170A	
VOLUME			MAX. 118dB			
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			LED STEADY/ FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v
	0.5~3	±0.05	±0.1	±0.2	-
	3~6			±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4
	0~10	±1°		±1°30'	
	10~50	±0°30'		±1°	
	50~120	±0°20'		±0°30'	
	120~400	±0°10'		±0°13'	
				±0°30'	

SURFACE FINISH		-	-	-	-	1	-
		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
		K.H.PARK	J.K.HAN		J.I.BAE	3	2023. 5. 3.
		TITLE			MODEL		
		SESAL-TI OUTLINE DRAWING			SESAL-TI		
					DWG. NO.		
					SESAL-TI_OUT		
		SCALE		SIZE	REV	SHEET	
		N/S		A4	00	1/1	

**Qlight**