MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				



MODEL NO		S125DML	
MATERIAL		HOUSING - ABS	
		LENS (GLOBE) - AS	
		LENS (GLOBE) - AS	
COLOR OF LENS		RED (O) , AMBER (O) , GREEN (O) , BLUE (O)	
FLASHES. PER MIN		60 ~ 80	
STROBE FLASHES. PER MIN		70 ~ 80	
REV. PER MIN		120 ~ 140	
KIND OF FUNCTION		FLASHES.	STROBE / REVOLVING
USE VOLT.	CURRENT	DC12~24V	MAX. 0.35A
		AC110 ~220V	MAX. 0.135A
KIND OF SOUND	WS	5 WARNING SOUNDS	
	WM	5 MELODIES	
	WA	5 ALRAMS	
	WV	5 VOICE SIGNALS	
VOLUME		Max.105dB at 1m	
PROTECTION GRADE		WATER & DUST PROOF IP54	
CABLE ENTRY		ϕ8 LEAD HOLE	
COLOR OF HOUSING		MARKED STANDARD	
ACTION		LED STEADY / FLASHING LIGHT	

ISO2768-1 : CLASS OF TOLERANCE					
		f	m	c	v
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-
	3~6			±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
	400~1000	±0.3	±0.8	±2	±4
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE FINISH

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
-	-	-	-	1	-

DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
J.Y. KIM	Y.H. JOO		J.K. HAN	3	2020.08.24

TITLE: S125DML LAYOUT

MODEL: S125DML

Qlight

DWG. NO.: S125DML LAYOUT

SCALE	SIZE	REV	SHEET
N/S	A4	00	1/1

A4(297X210)