



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO	ET64MCL		
MATERIAL	HOUSING-ABS		
	LENS-PC		
	BRACKET-ABS		
COLOR OF LENS	3 COLORS		
USE VOLT.	CURRENT	DC24V	0.067A
VOLUME	MAX. 85dB at 1m (BUZZER TYPE)		
PROTECTION GRADE	WATER & DUST PROOF IP20		
	WATER & DUST PROOF IP20 (BUZZER TYPE)		
CABLE ENTRY	φ10 LEAD HOLE		
COLOR OF HOUSING	MAKER STANDARD		
ACTION	LED STEADY LIGHT / FLASHING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH							
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY J.K.HAN	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.I.BAE	VIEW 3	DATE 2022.9.20		
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1								
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
	400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.		ET64MCL_OUT		
	10~50	±0°30'		±1°	±2°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1	
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								