MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				





MODEL NO	ETR50L		
MATERIAL	HOUSING-AL		
	LENS-PC		
	BRACKET-AL		
COLOR OF LENS	RED( ), AMBER( ), GREEN( )		
USE VOLT. / CURRENT	DC24V	0.055A	
VOLUME	MAX. 85dB at 1m (BUZZER TYPE)		
PROTECTION GRADE	WATER & DUST PROOF IP20		
	WATER & DUST PROOF IP20 (BUZZER TYPE)		
CABLE ENTRY	ϕ17 LEAD HOLE		
COLOR OF HOUSING	MAKER STANDARD		
ACTION	LED STEADY LIGHT / FLASHING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH
		f	m	ⓒ	v	
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
	400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE

DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
J.K.HAN	J.H.PARK		J.I.BAE	3	2022.9.20

TITLE	MODEL
ETR50L OUTLINE DRAWING	ETR50L
Qlight	DWG. NO. ETR50L_OUT

SCALE	SIZE	REV	SHEET
N/S	A4	00	1/1

A4(297X210)