



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO	EMCL50
MATERIAL	HOUSING-AL
	LENS-PC
COLOR OF LENS	3 COLORS
USE VOLT.	DC24V
VOLUME	MAX. 85dB at 1m (BUZZER TYPE)
PROTECTION GRADE	WATER & DUST PROOF IP69K(Buzzer Type IP20)
CABLE ENTRY	M12 CONNECTOR
COLOR OF HOUSING	MAKER STANDARD
ACTION	LED STEADY

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f	m	⊕	v
	3~6	±0.05	±0.1	±0.2	-
	6~30	±0.1	±0.2	±0.3	±0.5
	30~120	±0.15	±0.3	±0.5	±1
	120~400	±0.2	±0.5	±0.8	±1.5
	400~1000	±0.3	±0.8	±1.2	±2.5
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±2°	±4°
	10~50	±0°30'	±1°	±1°30'	±3°
	50~120	±0°20'	±1°	±1°30'	±2°
	120~400	±0°10'	±1°	±1°30'	±1°

SURFACE FINISH		Nr.		DWG. NO.		TITLE/ NAME		MAT'L		QT'Y		REFERENCE	
		DSND BY		CHKD BY		CHKD BY		APRV BY		VIEW		DATE	
		J.K.HAN		J.H.PARK				J.I.BAE		3		2022.9.20	
		TITLE		EMCL50		OUTLINE DRAWING		MODEL		EMCL50			
								DWG. NO.		EMCL50_OUT			
								SCALE		SIZE		REV	
								N/S		A4		00	
												SHEET	
												1/1	

Qlight