



MODEL NO	EMCL50U
MATERIAL	HOUSING-AL
	LENS-PC
COLOR OF LENS	3 COLORS
USE VOLT.	DC24V
VOLUME	MAX. 85dB at 1m (BUZZER TYPE)
PROTECTION GRADE	WATER & DUST PROOF IP67(Buzzer Type IP20)
CABLE ENTRY	M12 CONNECTOR
COLOR OF HOUSING	MAKER STANDARD
ACTION	LED STEADY

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH						
FOR LINEAR DIMENSIONS		f	m	⊙	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY J.K.HAN	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.I.BAE	VIEW 3	DATE 2022.9.20	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
	400~1000	±0.3	±0.8	±2	±4							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. EMCL50U_OUT			
	10~50	±0°30'		±1°	±2°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							