



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	EMCL50U-7C		
MATERIAL	HOUSING-AL		
	LENS-PC		
COLOR OF LENS	7 COLORS		
USE VOLT.	CURRENT	DC24V	0.041A
VOLUME	MAX. 85dB at 1m (BUZZER TYPE)		
PROTECTION GRADE	WATER & DUST PROOF IP20		
CABLE ENTRY	M12 CONNECTOR		
COLOR OF HOUSING	MAKER STANDARD		
ACTION	LED STEADY		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH								
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME			MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY J.K.HAN	CHKD BY J.H.PARK		APRV BY J.I.BAE	VIEW 3	DATE 2022.9.20		
	3~6			±0.3	±0.5									
	6~30	±0.1	±0.2	±0.5	±1									
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4										
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. EMCL50U-7C_OUT					
	10~50	±0°30'		±1°	±2°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1		
	50~120	±0°20'		±0°30'	±1°									
	120~400	±0°10'		±0°13'	±0°30'									