



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO		STC56ML				
MATERIAL		HOUSING-ABS				
		LENS-PC				
		POLE-AL				
COLOR OF LENS		CLEAR				
FLASHING PER MIN.		60 ~ 80				
USE VOLT.	LED	CURRENT	DC12V	0.08W	0.215A	
			DC24V		0.185A	
			AC110V		0.110A	
			AC220V		0.075A	
VOLUME		MAX. 90dB				
PROTECTION GRADE		WATER & DUST PROOF IP44(Buzzer Type IP23)				
CABLE ENTRY		ø8 LEAD HOLE				
COLOR OF HOUSING		MAKER STANDARD				
ACTION		MULTIPLE COLORS LED SIGNAL STEADY/ FLASHING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-					
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE					
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20					
	3~6			±0.3	±0.5												
	6~30	±0.1	±0.2	±0.5	±1		TITLE STC56ML OUTLINE DRAWING										
	30~120	±0.15	±0.3	±0.8	±1.5	MODEL STC56ML											
	120~400	±0.2	±0.5	±1.2	±2.5												
400~1000	±0.3	±0.8	±2	±4	DWG. NO. STC56ML_OUT												
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'							±3°						
	10~50	±0°30'		±1°							±2°						
	50~120	±0°20'		±0°30'							±1°	SCALE N/S					
	120~400	±0°10'		±0°13'	±0°30'	SIZE A4											
												REV 00		SHEET 1/1			