



MODEL NO		ETR50MCL	
MATERIAL		HOUSING-AL	
		LENS-PC	
		BRACKET-AL	
COLOR OF LENS		3 COLORS	
USE VOLT.	CURRENT	DC24V	0.085A
VOLUME		MAX. 85dB at 1m (BUZZER TYPE)	
PROTECTION GRADE		WATER & DUST PROOF IP20	
		WATER & DUST PROOF IP20 (BUZZER TYPE)	
CABLE ENTRY		ø17 LEAD HOLE	
COLOR OF HOUSING		MAKER STANDARD	
ACTION		LED STEADY LIGHT / FLASHING LIGHT	

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH							
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY J.K.HAN	CHKD BY J.H.PARK		APRV BY J.I.BAE	VIEW 3	DATE 2022.9.20		
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1								
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
	400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	<div>ETR50MCL OUTLINE DRAWING</div> 			MODEL ETR50MCL				
	10~50	±0°30'		±1°	±2°				DWG. NO. ETR50MCL_OUT				
	50~120	±0°20'		±0°30'	±1°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1	
	120~400	±0°10'		±0°13'	±0°30'								