



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			SNELR		
MATERIAL			HOUSING-AL		
			LENS-TEMPERED GLASS		
			PROTECTION CAGE-SUS316L		
			REFLECTOR-PC		
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )		
REV. PER MIN.			120~140		
USE VOLT.	LED	CURRENT	DC12V	1W	0.183A
			DC24V		0.127A
			AC110V		0.035A
			AC220V		0.017A
PROTECTION GRADE			WATER & DUST PROOF IP66		
CABLE ENTRY			1/2" NPT		
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2		
ACTION			LED REVOLVING WARNING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-		-		1		-	
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L		QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20			
	3~6			±0.3	±0.5									
	6~30	±0.1	±0.2	±0.5	±1									
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4										
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°					DWG. NO.		SNELR_OUT		
	10~50	±0°30'		±1°	±2°					SCALE N/S				
	50~120	±0°20'		±0°30'	±1°									
	120~400	±0°10'		±0°13'	±0°30'									

**Qlight**

A4(297X210)