



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			MRA60-R-12 / MRA60-R-24			
MATERIAL			PC			
COLOR OF LENS			POWER OFF	MILK OPACITY		
			POWER ON	R(), A(), G(), B(), W()		
FLASHES. PER MIN			60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V	1.2W	0.085A	
			DC24V		0.050A	
PROTECTION GRADE			WATER & DUST PROOF IP65			
ACTION			LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-		-		-	
FOR LINEAR DIMENSIONS		f	(m)	c	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5		H.M.SEO	Y.H.JOO		J.W.KIM	3	2022.06.14
	6~30	±0.1	±0.2	±0.5	±1		TITLE		MODEL			
	30~120	±0.15	±0.3	±0.8	±1.5		MRA60-R		MTR60 SERIES			
	120~400	±0.2	±0.5	±1.2	±2.5		OUTLINE DRAWING		DWG. NO.			
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4				MRA60-R_OUT			
	0~10	±1°	±1°30'	±3°					SCALE	SIZE	REV	SHEET
	10~50	±0°30'	±1°	±2°					N/S	A4	00	1/1
	50~120	±0°20'	±0°30'	±1°								
	120~400	±0°10'	±0°13'	±0°30'								

A4(297X210)