



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			MG60-R,A,G,B,W-12 / MG60-R,A,G,B,W-24		
MATERIAL			PC		
COLOR OF LENS			R(),A(),G(),B(),W()		
FLASHES. PER MIN			60 ~ 80		
USE VOLT.	LED	CURRNET	DC12V	1.2W	0.085A
			DC24V		0.050A
PROTECTION GRADE		WATER & DUST PROOF IP65			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	-	-
FOR LINEAR DIMENSIONS		f	(m)	c	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY H.M.SEO	CHKD BY Y.H.JOO	CHKD BY 	APRV BY J.W.KIM	VIEW 3	DATE 2022.06.14
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1		TITLE MG60 OUTLINE DRAWING		MODEL MTG60 SERIES			
	30~120	±0.15	±0.3	±0.8	±1.5					DWG. NO. MG60_OUT		
	120~400	±0.2	±0.5	±1.2	±2.5						SCALE N/S	SIZE A4
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							