



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			MC60-R,A,G,B,W-12 / MC60-R,A,G,B,W-24		
MATERIAL			PC		
COLOR OF LENS			POWER OFF	TRANSPARENT LENS	
			POWER ON	R(), A(), G(), B(), W()	
FLASHES. PER MIN			60 ~ 80		
USE VOLT.	LED	CURRNET	DC12V	1.2W	0.085A
			DC24V		0.050A
PROTECTION GRADE		WATER & DUST PROOF IP65			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	-	-		
FOR LINEAR DIMENSIONS		f	(m)	c	v		Nr.	DWG. NO.	TITLE/ NAME			MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY H.M.SEO	CHKD BY Y.H.JOO	CHKD BY 	APRV BY J.W.KIM	VIEW 3	DATE 2022.06.14		
	3~6			±0.3	±0.5									
	6~30	±0.1	±0.2	±0.5	±1									
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4										
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.					
	10~50	±0°30'		±1°	±2°				MC60_OUT					
	50~120	±0°20'		±0°30'	±1°				SCALE N/S					
	120~400	±0°10'		±0°13'	±0°30'				SIZE A4					
									REV 00					
									SHEET 1/1					