



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO			SEALR			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED CLASS			
			REFLECTOR-PC			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	LED	CURRENT	DC24V	1W	MAX. 0.127A	
			AC110V		MAX. 0.035A	
			AC220V		MAX. 0.017A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5		S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		SEALR OUTLINE DRAWING			SEALR		
	120~400	±0.2	±0.5	±1.2	±2.5					DWG. NO.		
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4					SEALR_OUT		
	0~10	±1°	±1°30'	±1°30'	±3°					SCALE	SIZE	REV
	10~50	±0°30'	±1°	±1°	±2°					N/S	A4	00
	50~120	±0°20'	±0°30'	±0°30'	±1°					SHEET		
	120~400	±0°10'	±0°13'	±0°30'	±0°30'					1/1		