



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			MR60-R,A,G,B,W-12 / MR60-R,A,G,B,W-24		
MATERIAL			PC		
COLOR OF LENS			POWER OFF	MILK OPACITY	
			POWER ON	R(), A(), G(), B(), W()	
FLASHES. PER MIN			60 ~ 80		
USE VOLT.	LED	CURRNET	DC12V	1.2W	0.085A
			DC24V		0.050A
PROTECTION GRADE		WATER & DUST PROOF IP65			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	-	-					
FOR LINEAR DIMENSIONS		f	(m)	c	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE					
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE						
	3~6			±0.3	±0.5	H.M.SEO	Y.H.JOO		J.W.KIM	3	2022.06.14						
	6~30	±0.1	±0.2	±0.5	±1	TITLE MR60 OUTLINE DRAWING											
	30~120	±0.15	±0.3	±0.8	±1.5							MODEL MTR60 SERIES					
	120~400	±0.2	±0.5	±1.2	±2.5												
400~1000	±0.3	±0.8	±2	±4													
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'							±3°	DWG. NO. MR60_OUT					
	10~50	±0°30'		±1°							±2°						
	50~120	±0°20'		±0°30'							±1°						
	120~400	±0°10'		±0°13'							±0°30'						
						SCALE N/S		SIZE A4	REV 00	SHEET 1/1							

A4(297X210)