



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			MC70-R,A,G,B,W-12 / MC70-R,A,G,B,W24		
MATERIAL			PC		
COLOR OF LENS			POWER OFF	TRANSPARENT LENS	
			POWER ON	R(),A(),G(),B(),W()	
FLASHES. PER MIN			60 ~ 80		
USE VOLT.	LED	CURRNET	DC12V	1.2W	0.085A
			DC24V		0.050A
PROTECTION GRADE		WATER & DUST PROOF IP65			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	-	-								
FOR LINEAR DIMENSIONS		f	(m)	c	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE								
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE								
	3~6			±0.3	±0.5		H.M.SEO	Y.H.JOO		J.W.KIM	3	2022.06.14								
	6~30	±0.1	±0.2	±0.5	±1	TITLE MC70 OUTLINE DRAWING														
	30~120	±0.15	±0.3	±0.8	±1.5							MODEL MTC70 SERIES								
	120~400	±0.2	±0.5	±1.2	±2.5															
400~1000	±0.3	±0.8	±2	±4																
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°							DWG. NO. MC70_OUT									
	10~50	±0°30'	±1°	±2°																
	50~120	±0°20'	±0°30'	±1°													SCALE N/S			
	120~400	±0°10'	±0°13'	±0°30'																
						REV 00		SHEET 1/1												

A4(297X210)