



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			MR70-R,A,G,B,W-12 / MR70-R,A,G,B,W24		
MATERIAL			PC		
COLOR OF LENS			POWER OFF	MILK OPACITY	
			POWER ON	R(),A(),G(),B(),W()	
FLASHES. PER MIN			60 ~ 80		
USE VOLT.	LED	CURRNET	DC12V	1.2W	0.085A
			DC24V		0.050A
PROTECTION GRADE		WATER & DUST PROOF IP65			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH					
FOR LINEAR DIMENSIONS	0.5~3	f	(m)	c	v						
	3~6	±0.05	±0.1	±0.2	-						
	6~30	±0.1	±0.2	±0.5	±1						
	30~120	±0.15	±0.3	±0.8	±1.5						
	120~400	±0.2	±0.5	±1.2	±2.5						
	400~1000	±0.3	±0.8	±2	±4						
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°						
	10~50	±0°30'		±1°	±2°						
	50~120	±0°20'		±0°30'	±1°						
	120~400	±0°10'		±0°13'	±0°30'						

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
H.M.SEO	Y.H.JOO		J.W.KIM	3	2022.06.14
TITLE			MODEL		
MR70 OUTLINE DRAWING			MTR70 SERIES		
			DWG. NO.		
			MR70_OUT		
SCALE		SIZE	REV	SHEET	
N/S		A4	00	1/1	

A4(297X210)