



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO		SMP35-N		
MATERIAL		HOUSING-ABS		
		RESONANCE CHAMBER-ABS		
		BRACKET-SUS		
COLOR OF HOUSING		MAKER STANDARD		
USE VOLT.	CURRNET	DC12V ~ 24V	MAX. 0.680A	
		AC110V ~ 220V	MAX. 0.170A	
KIND OF SOUND	VOLUME	WARNING SOUNDS 30Ch	MAX. 115dB at 1m	
PROTECTION GRADE		WATER & DUST PROOF - IP65		
CABLE ENTRY		ø21 CABLE ENTRY		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH					
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY
	3~6	±0.05	±0.1	±0.3	±0.5			H.M.SEO	J.Y.KIM		J.W.KIM
	6~30	±0.1	±0.2	±0.5	±1						
	30~120	±0.15	±0.3	±0.8	±1.5						
	120~400	±0.2	±0.5	±1.2	±2.5						
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4			TITLE SMP35-N OUTLINE DRAWING			
	0~10	±1°	±1°30'	±3°				MODEL SMP35-N			
	10~50	±0°30'	±1°	±2°				DWG. NO. SMP35-N_OUT			
	50~120	±0°20'	±0°30'	±1°				SCALE	SIZE	REV	SHEET
	120~400	±0°10'	±0°13'	±0°30'				N/S	A4	00	1/1

**Qlight**

A4(297X210)