



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO		SMP50-N	
MATERIAL		HOUSING-ABS	
		RESONANCE CHAMBER-ABS	
		BRACKET-SUS	
COLOR OF HOUSING		MAKER STANDARD	
USE VOLT.	CURRNET	DC12V~24V	MAX. 2.800A
		AC110V ~ 220V	MAX. 0.540A
KIND OF SOUND	VOLUME	WARNING SOUNDS 30Ch	MAX. 123dB at 1m
PROTECTION GRADE		WATER & DUST PROOF - IP65	
CABLE ENTRY		ø21 CABLE ENTRY	

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-									
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME			MAT'L		QTY	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY H.M.SEO	CHKD BY J.Y.KIM	CHKD BY 	APRV BY J.W.KIM	VIEW 3	DATE 2022.12.23					
	3~6			±0.3	±0.5											
	6~30	±0.1	±0.2	±0.5	±1											
	30~120	±0.15	±0.3	±0.8	±1.5											
	120~400	±0.2	±0.5	±1.2	±2.5											
400~1000	±0.3	±0.8	±2	±4												
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°											
	10~50	±0°30'		±1°	±2°											
	50~120	±0°20'		±0°30'	±1°											
	120~400	±0°10'		±0°13'	±0°30'											
TITLE									SMP50-N OUTLINE DRAWING			MODEL		SMP50-N		
												DWG. NO.		SMP50-N_OUT		
												SCALE N/S	SIZE A4	REV 00	SHEET 1/1	

Qlight

A4(297X210)