



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO			SSL300W			
MATERIAL			HOUSING-AL			
			LENS-PC			
COLOR OF LENS			RED, AMBER, GREEN			
USE VOLT.	LED	CURRENT	DC24V	0.08W	0.453A	
			AC110V		0.120A	
			AC220V		0.120A	
PROTECTION GRADE			WATER & DUST PROOF IP68			
CONNECTOR			M12-5PIN or C10 CABLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-			
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE		
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY C.S.GWAK	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2021.08.30				
	3~6			±0.3	±0.5										
	6~30	±0.1	±0.2	±0.5	±1										
	30~120	±0.15	±0.3	±0.8	±1.5										
	120~400	±0.2	±0.5	±1.2	±2.5										
400~1000	±0.3	±0.8	±2	±4											
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°					DWG. NO. SSL300W_OUT					
	10~50	±0°30'		±1°	±2°					SCALE 1/1			SIZE A4	REV 01	SHEET 1/1
	50~120	±0°20'		±0°30'	±1°										
	120~400	±0°10'		±0°13'	±0°30'										