



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			QAD100H-N			
MATERIAL			HOUSING-ABS			
			LENS-PC			
			-			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHES. PER MIN			60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V~24V	0.5W	MAX.1.270A	
			AC110V~220V		MAX.0.255A	
VOLUME			MAX. 100dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP65			
CABLE ENTRY			ø10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-	
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY H.M.SEO	CHKD BY J.Y.KIM	CHKD BY 	APRV BY J.W.KIM	VIEW 3	DATE 2022.12.23	
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1								
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
400~1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°					DWG. NO. QAD100H-N_OUT			
	10~50	±0°30'		±1°	±2°					SCALE N/S			
	50~120	±0°20'		±0°30'	±1°	SIZE A4							
	120~400	±0°10'		±0°13'	±0°30'	REV 00							
						SHEET 1/1							

**Qlight**

A4(297X210)