



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			QAD125H-N			
MATERIAL			HOUSING-ABS			
			LENS-PC			
			-			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHES. PER MIN			60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V~24V	0.5W	MAX.1.130A	
			AC110V~220V		MAX.0.275A	
VOLUME			MAX. 115dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP65			
CABLE ENTRY			φ10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH						
FOR LINEAR DIMENSIONS		f	m	(C)	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	1
	0.5~3	±0.05	±0.1	±0.2	-							
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1		DSND BY	CHKD BY			APRV BY	VIEW
	30~120	±0.15	±0.3	±0.8	±1.5		H.M.SEO	J.Y.KIM			J.W.KIM	3
	120~400	±0.2	±0.5	±1.2	±2.5							DATE
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4		TITLE		QAD125H-N		MODEL	
	0~10	±1°	±1°30'	±3°			OUTLINE DRAWING				QAD125H-N	
	10~50	±0°30'	±1°	±2°			Qlight		DWG. NO.		QAD125H_OUT	
	50~120	±0°20'	±0°30'	±1°					SCALE		REV	
	120~400	±0°10'	±0°13'	±0°30'					N/S		00	
									SIZE		SHEET	
									A4		1/1	

A4(297X210)