



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	EMCL50T		
MATERIAL	HOUSING-AL		
	LENS-PC		
COLOR OF LENS	3 COLORS		
USE VOLT.	CURRENT	DC12~24V	0.040A
VOLUME	MAX. 85dB at 1m (BUZZER TYPE)		
PROTECTION GRADE	WATER & DUST PROOF IP69K		
CABLE ENTRY	M12 CONNECTOR		
COLOR OF HOUSING	MAKER STANDARD		
ACTION	LED STEADY		

NO	색 상		결 선
	접촉전	접촉시	
1	무색(NONE)	적색(RED)	pin1 + pin4
2	녹색(GREEN)	황색(YELLOW)	pin1 + pin3 + pin4

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH						
FOR LINEAR DIMENSIONS		f	m	⊙	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY J.K.HAN	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.I.BAE	VIEW 3	DATE 2022.10.14	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
	400~1000	±0.3	±0.8	±2	±4							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. EMCL50T_OUT			
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	120~400	±0°10'		±0°13'	±0°30'							